

PowerVerter *24Vdc to 12Vdc* Converters

24Vdc to 12Vdc Converters

These products offer a convenient way to operate mass produced 12Vdc equipment, such as cell phones, in car entertainment equipment, professional communication equipment, telematics equipment, refrigerators, televisions, etc. from the 24Vdc mobile electrical systems found on diesel engined vehicles and vessels and the 28Vdc systems found on aircraft.

These cool running products use switch mode technology and are assembled using surface mount technology.

All the products are CE marked, e marked and meet the requirements of FCC Class B.

A Comprehensive 24Vdc to 12Vdc Converter Range

This leaflet covers the PowerVerter series, ten products from 3 Amps to 30 Amps in isolated or common earth configurations. They have been optimised for high volume 24Vdc to 12Vdc applications such as on heavy goods vehicles, coaches, buses, construction, forestry and agricultural vehicles, commercial vessels, yachts and many types



proportional to temperature so high efficiency leads to high reliability. The Mean Time Between Failure figure is around 160 years!

Rugged and Compact

The converters are enclosed in a rugged aluminum extrusion. The low mass Surface Mount Technology components are also less prone to damage from vibration and shock, further increasing the reliability of the units. The use of SMT results in a very compact unit, making it easier for the installer to find a convenient location.

Tamper Proof

There are no ventilation holes to permit stray objects, dust or water droplets to enter the case. There are no external fuses to be tampered with. Fuses will only blow if there is a fault so there is no need to make them accessible.

Fast Installation

All the units consume an off load current of less than 15mA, which is probably less than the self discharge current of the vehicle's battery. In most cases this can be ignored, speeding the installation by removing the need to fit a remote switch.

The low heat dissipation allows them to be mounted in less well ventilated positions which makes installation easier.

All the products fit onto a 'Click 'n' Fit' mounting clip which is fixed in three points allowing it to be mounted on uneven surfaces. It is easy to fit the clip into awkward places and then simply click the unit into position.

A red LED indicates when there is output from the converter. This gives reassurance to the installation engineer and speeds fault finding.

Secure Isolation

It's your choice. The PowerVerter range offers an isolated option at every power rating. Some vehicle manufacturers, such as Scania, require that "the converter shall be ground loss protected". This means that the output voltage shall not exceed the specification if the supply ground connection and/or the load ground connection is lost. This requires an isolated converter. Isolated converters also prevent a direct connection between the 24Vdc input and the 12Vdc appliance in the case of a semiconductor failure.

Cool Running

The converters operate with a power conversion efficiency as high as 93%. This results in very little heat being generated. The reliability of semiconductors is inversely



Product Coding

The product code is developed as follows, taking the PV3i as an example:

PV	PowerVerter 24Vdc to 12Vdc converter
3	3 amps continuous output (12Vdc output at 3 amps)
i	Isolated between input and output (s indicates switchmode, non-isolated)



for use on vehicles, vessels and aircraft

Choose *your* PowerVerter

All PowerVerter convert 24Vdc to 12Vdc		Isolation	
		Non-Isolated Common Negative	Isolated Input to Output
Load current Continuous/ intermittent	3/6A	PV3s	PV3i
	6/10A	PV6s	PV6i
	12/18A	PV12s	PV12i
	18/21A	PV18s	PV18i
	24/30A	PV24s	PV24i

The intermittent current may be drawn for a maximum of 2 minutes followed by 8 minutes rest.

Technical *data*

Model	Size	Weight	Model	Size	Weight
PV3s	67 x 87 x 50mm	225g	PV18s, PV24s, PV12i	167 x 87 x 50mm	620g
PV6s, PV3i	89 x 87 x 50mm	270g/290g			590g
PV12s, PV6i	127 x 87 x 50mm	405g	PV18i, PV24i	217 x 87 x 50mm	835g

Common Characteristics

Input voltage range	17 to 32Vdc
Output voltage	13.6Vdc +15% and -20% at extremes of temperature, load, input tolerance, etc
Transient voltage protection	Meets ISO7637-2 International Standard for 24Vdc Commercial Vehicles
Electro static voltage protection	Meets ISO10605, ISO14982, >8kV contact, 15kV discharge
Output noise	<50mV pk-pk at continuous load. Meets CISPR25
Off load current	<15mA
Power conversion efficiency	Typically: 90% for non-isolated units, 85% for isolated units
Isolation	>400Vrms between input, output and case, on isolated products only
Mean time between failures	>162 years (HRD4)
Operating temperature	-25°C to +30°C to meet this specification table. +30°C to +80°C de-rate linearly to 0A
Storage temperature	-25°C to +100°C
Operating humidity	95% max, non-condensing
Casework	Anodised Aluminium, Glass Filled Polycarbonate. Dust water and impact resistance IP533
Connections	Four 6.3mm push-on flat blade connectors
Output indicator	Red LED adjacent to output terminals
Mounting method	'Click 'n' Fit' mounting clip, fitted separately using three hole fixing
Safe area protection:	Over current Over heat Transients Catastrophic failure
	Limited by current sensing circuit Limited by temperature sensing circuit Protected by filters and rugged component selection Protected by internal input and output fuses
Approvals	89/336/EEC The EMC Directive 95/54/EC The Automotive EMC Directive 93/68/EEC The CE Marking Directive VIDG5 AES For use on Police and Fire Vehicles
Tested to	ISO7637-2, ISO10605, ISO14982, ISO11451, ISO11452, CISPR 25, VDE0879-3, EN60945 Annex A
Markings	CE Marked and e Marked No. eII 990324



AlfaTronix Limited 29 Newtown Business Park, Poole, Dorset BH12 3LL, Great Britain, European Union
 Telephone: +44 (0) 1202 715517. Fax: +44 (0) 1202 715122. E-mail: sales@alfatronix.ltd.uk
 Website: <http://www.alfatronix.ltd.uk>
 An ISO9001 Registered Company